

## EDGE

### FORUM LED Edge Light Recess Lighting

#### Features

##### Body

The LED fixture features a lightweight aluminum frame, designed to prevent light leakage. The frame houses LED chips and opal PMMA lens for soft illumination. The Light Emitting Surface (LES) Glare-Guard Technology which reduces glare by 60% while keeping the same light distribution from a flat panel.

##### LED Characteristics

Bright LED modules that maintains uniform intensity producing up to 124 lumens per watt, with a typical CRI of 80+. Available in 3000 K, 3500 K and 4000 K color temperatures.

##### Dimming

100%~10% dimming capability. This fixture is compatible with industry standard 0-10V dimmers (contact factory for listing of compatible

dimmers).

##### Beam Spread

The fixture lens provides 110° beam spread.

##### Mounting

Easy mounting in standard size T-bar ceilings. Standard ceiling tiles can be mounted onto the center cavity of the fixture.

##### LED Driver

Remote mounted driver available in 120V, 120~277V and 347V. Driver power factor is 0.95 min with less than 20 THD. Includes user selectable wattage and color temperature switches.


##### Operating Temperature

-20°C~40°C (-4°F~104°F)

##### Environment


- For indoor use only.
- Suitable for damp locations.
- I.C. rated.

Light Size	Wattage	Lumens / Color Temp		
		3000 K	3500 K	4000 K
1'x1'	20W	2100	2300	2200
1'x2'	30W	3100	3400	3200
1'x4'	20W	2100	2200	2200
	30W	3100	3200	3200
	40W	4000	4200	4200
2'x2'	20W	2100	2200	2200
	30W	3100	3200	3200
	40W	4000	4200	4200
2'x4'	30W	3300	3500	3400
	40W	4300	4600	4500
	50W	5200	5700	5400
30"×30"	20W	2200	2200	2300
	30W	3100	3300	3300
	40W	4100	4400	4400



#### Description

These LED Edge lights promote the art of omission. It seamlessly integrates into existing elements in any space to facilitate a type of minimalism, while maintaining a functional form that transcends into the surroundings.



Part No.	Outer Length (L1)	Inner Length (L2)	Outer Width (W1)	Inner Width (W2)
EDGE-11-WH	11 3/4" (298mm)	10 5/8" (277mm)	11 3/4" (298mm)	10 5/8" (277mm)
EDGE-12-WH	11 3/4" (298mm)	10 5/8" (277mm)	23 3/4" (603mm)	22 1/8" (582mm)
EDGE-14-WH	11 3/4" (298mm)	10 5/8" (277mm)	47 1/8" (1212mm)	46 7/8" (1191mm)
EDGE-22-WH	23 3/4" (603mm)	22 1/8" (582mm)	23 3/4" (603mm)	22 1/8" (582mm)
EDGE-24-WH	23 3/4" (603mm)	22 1/8" (582mm)	47 1/8" (1212mm)	46 7/8" (1191mm)
EDGE-33-WH	29 3/4" (756mm)	28 1/8" (735mm)	29 3/4" (756mm)	28 1/8" (735mm)



**Notes:** Accessories are sold separately. For additional options please consult your Liteline representative. Due to our continued efforts to improve our products, product specifications are subject to change without notice.

#### Ordering Guide

